
# alca

# APV102 Floor drain 105×105/50 mm side outlet, stainless steel grid, wet odour trap





#### Application

For wheelchair access

For the interior, where will be frequent use associated with the regular water runoff into the floor drain (bathrooms)

Features

- Side connection to waste Ø50 mm
- Compatibility with floor drains parts including wet, dry and combined odour trap SMART
- Solid brass grid 102×102×4 mm
- Material: stainless steel AISI 304, DIN 1.4301
- Material: polypropylene resistant to mechanical, chemical and thermal damage
- Mechanically cleanable trap up to the waste pipe
- Wide insulation collar for connection to waterproofing construction
- Wet odour trap prevents the penetration of odours from the sewer
- Height adjustable throat 9–95 mm

## Scope of supply

- Design stainless steel grid
- Floor drain throat 105×105 mm
- Seal kit
- Floor drain body Ø50 mm, side outlet
- Wet odour trap

## Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)
APV102	8594045930412	0,97   7,79   175,7 kg	230×190×230   780×245×475 mm	8   160 pcs
Warranty	Norms			
2/6 years *	EN 1253			

Taskatast

Technical specifications Total installation height 88-174

- Total installation height 88-174 mm
  Besistance of odour trap against the pressure
- Resistance of odour trap against the pressure 480 Pa
- Waste pipe diameter 50 mm
  Flow of the inlet grid 46 l/min
- Flow of the inlet grid 46 l/min
- Load class K3 300 kg
- Odour trap 51 mm