





### Application

For mounting as high, medium and low-lying For installation on plaster

#### Features

- Design solution ensures the comfort when flushing even for children and handicapped people
- Material: ABS
- The cistern is isolated against condensation
- Volume 8 I with a large variety of settings for the flushing water volume
- Water supply from left/right
- Flushing DUAL 3/6 I
- Universal brackets with their spacing and shape are consistent with existing tanks

# Water saving setting

- Scope of supply
- Fixation set: screw Ø5×40 2 pcs, dowel Ø8 2 pcs
- Elbow Ø50/40 mm for the low-lying cistern
- Tank:
- Fill (1/2") and flush valves
- Flush set for low level tank installations (button small, large)
- Flush set for the high-lying cistern (cord, handle, lever)

## Order number, Logistic information

Code	EAN	Weight (piece   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
A93-1/2"	8594045931051	2,87   2,87   186,4 kg	456×410×142   - mm	1   58 pcs

Warranty	Norms
2/3 years *	EN 14124, EN 14055

### Technical specifications

- Acoustic group II <30 dB</p>
- Recommended operating pressure 0,5-0,8 MPa
- Functional requirements class I
- Small flush 2,5-3,5 l
- Working range 0,05-1,6 MPa
- When installed in a high rise position the tank is functional only with the big flush 6-8 l
- Factory setting of small flush 3 I
- Factory setting of large flush 6 l
- Big flush 5,5-8 l