


A94-1/2"

Universal WC cistern ALCA UNI START/STOP



Application

For mounting as high, medium and low-lying
For installation on plaster

Features

- Design solution ensures the comfort when flushing even for children and handicapped people
- Material: ABS
- The cistern is isolated against condensation
- Volume 8 l with a large variety of settings for the flushing water volume
- Water supply from left/right
- Flushing START/STOP
- Universal brackets with their spacing and shape are consistent with existing tanks
- Water saving setting

Scope of supply

- Fixation set: screw Ø5×40 – 2 pcs, dowel Ø8 – 2 pcs
- Elbow Ø50/40 mm for the low-lying cistern
- Tank:
- Fill (1/2") and flush valves
- Flush set for low level cistern installation (button)
- Flush set for the high-lying cistern (cord, handle, lever)

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
A94-1/2"	8594045936827	2,88 2,88 186,8 kg	456×410×142 – mm	1 58 pcs

Warranty 2/3 years *	Customs code 39229000	Norms EN 14124, EN 14055
--------------------------------	---------------------------------	------------------------------------

Technical specifications

- Acoustic group II <30 dB
- Recommended operating pressure 0,5-0,8 MPa
- Functional requirements class I
- Working range 0,05-1,6 MPa
- When installed on a high level cistern STOP system is not functional
- Flushing 6-8 l