

APZ4-1150 Flexible

Shower drain with an edge for perforated grids and adjustable vertical flange to the wall

Application

- For wheelchair access
- For drainage of floor-level showers
- For installation directly to the wall
- For perforated grids
- For indoor use

Features

- Better and safer transition of the insulation from the floor to the wall
- The collar and trap are protected by foil, and the channel itself by a polystyrene insert
- Trap material: polypropylene
- Shower drain material: stainless steel 2 mm, AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Possibility to buy a combined odour trap
- Adjustable vertical insulating collar for tiles with a thickness of 6–12 mm
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Self-adhesive tape for quality waterproofing
- Trap firmly connected to the drain – 100% waterproofing
- Installation height from 85 mm
- Facilitates the inclination of the floor
- Adjustable height
- The high flow rate is achieved due to the double compartment trap system

25 years guarantee

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
APZ4-1150	8595580500023	5,46 43,64 150,9 kg	1220x160x205 mm	8 24 pcs

- Installation trough cover – polystyrene
- Protective foil covering for the drainage edges and odour trap
- Protective film for trap inlet

Technical specifications

- Self-adhesive waterproofing tape
- Total installation height 100–158 mm
- The shower drain is assembled with the odour trap
- Minimum thickness of concrete 85 mm
- Resistance of odour trap against the pressure 982 Pa
- Waste pipe diameter 50 mm
- Movable flange range 10–15 mm
- Flow rate 60–68,8 l/min
- Load class K3 300 kg
- Odour trap 50 mm

