

APZ5-TWIN-650 Spa

Waste system for installation in walls, cover for embedding tiles

Application

For wheelchair access

For installation into the wall

Suitable for areas with movement of large number of people - swimming pools,

spa, wellness center

Features

- Easily removable cover for embedding tiles
- The collar and trap are protected by foil, and the channel itself by a polystyrene
- Trap material: polypropylene
- Material of drainage channel: stainless steel AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Possibility to buy a combined odour trap
- Possibility to order with LED backlight
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Self-adhesive waterproofing tape for quality waterproofing
- The trap is firmly connected to the drain channel 100% waterproofing
- Installation depth 64 mm
- The system is placed outside the area of mechanical stress
- Water flows into the drain only between the edge of the floor tiles and the cover of the drain system
- The high flow rate is achieved due to the double compartment trap system
- 25 years guarantee

Scope of supply

- Anchoring set for fixing the adjustable legs: screw M6×12 2 pcs
- Installation channel cover
- Anchoring set: screw Ø6×50 2 pcs, dowel Ø10 2 pcs, screw Ø4,2×38 3 pcs, dowel Ø8 - 3 pcs


EN 1253

- Stainless steel cover for embedding tiles
- The collar and the odour trap inlet are covered by the protective foil
- Self-adhesive waterproofing tape
- The shower drain is assembled with the odour trap

Customs code

39229000





Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(kus packing palett)	(piece packing)	(packing palett)
APZ5-TWIN-650	8595580500139	4,4146 0,0000 0,0000 kg	720×160×205 mm	8 24 pcs

2/25 years **Technical specifications**

Guarantee

- Total installation height 60 mm
- Waste pipe diameter 50 mm
- Flow rate 60-68,8 I/min
- Installation depth 85 mm
- Odour trap 50 mm