

A101/1300H Sádromodul

Pre-wall installation system for dry build up (plasterboard) – for people with reduced mobility

Application

For mounting in front of a support wall or in to a plasterboard construction – for

people with reduced mobility

For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm

mm

To mount supporting handrails

For floor thickness 0–200 mm

For use with remote or sensor flushing

For wall-hung WC

Features

- Dual flush, independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The frame allows the anchoring to a separate sufficiently strong plasterboard partition, in front of the bearing wall
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Frame material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- Suitable for installation of remote or sensor flushing
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable telescopic feet, range 0–200 mm
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from the rear/top
- Frame for hanging wall-hung WC with boards for installation of handles for people with reduced mobility
- Maintenance work without using any tools
- Mounting depth 125 mm, with waste elbow 160 mm
- Mounting boards made of waterproof glued plywood

Scope of supply

- Boards for installing handrails for the disabled – 2 pcs
- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8×60 - 12 pcs, anchor Ø12 - 12 pcs
- Elbow waste connector HT 90/90 polyethylene, PE-HD
- Service opening cover is simply adjustable, screws 4 pcs
- Cistern with fill and flush valve
- Waste reduction HT 90/110 polyethylene, PE-HD
- End-caps set for protecting the connecting holes during installation of the system
- Self-supporting frame
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
A101/1300H	8595580500559	33,90 33,90 189,5 kg	1195×145×1060 1195×1060×145 mm	1 5 pcs

Warranty

2/6 years *

Customs code

39229000

Norms

EN 14124, EN 14055, EN ISO 10535, 732030

Technical specifications

- Recommended range of water pressure 0,3–0,5 MPa
- Functional range of water pressure 0,05–0,8 MPa
- Hygienic reserve 3 l
- Small flush 2,5–3,5 l
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2"
- Factory setting of small flush 3 l
- Factory setting of large flush 6 l
- Big flush 6–9 l
- Load test 400 kg

