


# **APV5211**

## Floor drain 150×150/50 mm side outlet, grey grid, wet odour trap





#### Application

For wheelchair access

For drainage of floor level showers

For the interior, where will be frequent use associated with the regular water

runoff into the floor drain (bathrooms)

#### **Features**

- Side connection to waste Ø50 mm
- Insulation collar for connection to waterproofing of the building
- Compatibility with floor drains parts including wet, dry and combined odour trap SMART
- Material: polypropylene resistant to mechanical, chemical and thermal damage
- Mechanically cleanable trap up to the waste pipe
- Plastic grid 145×145×5 mm
- Wet odour trap prevents the penetration of odours from the sewer
- Height adjustable throat 22–110 mm

## Scope of supply

- Floor drain throat 150×150 mm
- Plastic grid gray
- Seal kit
- Floor drain body Ø50 mm, side outlet
- Wet odour trap

### Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)
APV5211	8595580507107	0,59   8,92   162,7 kg	300×150×190   590×430×390 mm	15   240 pcs

Warranty Customs code Norms 2/6 years \* 39269097 EN 1253

## **Technical specifications**

- Total installation height 101-189 mm
- Resistance of odour trap against the pressure 480 Pa
- Waste pipe diameter 50 mm
- Flow of the inlet grid 46 l/min
- Wet odour trap 51 mm