
alca

APV6411 Floor drain 150×150/50 mm straight outlet, stainless steel grid, wet odour trap





Application

For wheelchair access

For the interior, where will be frequent use associated with the regular water

runoff into the floor drain (bathrooms)

Features

- Insulation collar for connection to waterproofing of the building
- Compatibility with floor drains parts including wet, dry and combined odour trap SMART
- Material: stainless steel AISI 304, DIN 1.4301
- Material: polypropylene resistant to mechanical, chemical and thermal damage
- Mechanically cleanable trap up to the waste pipe
- Stainless steel grid 143×143×5 mm
- Straight connection to waste Ø50 mm
- Wet odour trap
- Height adjustable throat 22–110 mm
- Scope of supply
- Floor drain throat 150×150 mm
- Stainless steel grid
- Seal kit
- Drain body Ø50 mm, straight outlet
- Wet odour trap

Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
APV6411	8595580520779	0,65 9,76 176,2 kg	300×160×170 590×430×390 mm	15 240 pcs
Warranty	Norms			
2/6 years *	EN 1253			

2/6 years *

Technical specifications

Total installation height 151-239 mm

- Resistance of odour trap against the pressure 480 Pa
- Waste pipe diameter 50 mm
- Flow of the inlet grid 46 l/min

Wet odour trap 51 mm

1