

# **A564CRM1**

# Bath pop-up waste and trap, with overflow filler, chrome

### Application

For filling the bath by overflow To drain the water from the bath to the waste For bathtubs with drain outlet Ø52 mm For standard size bathtubs

- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 57 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub only control knob visible
- Control shaft made of stainless steel
- Aerator Neoperl easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow


### Scope of supply

- Assembly kit
- Chrome-plated brass outlet grid Chrome-plated plastic control knob Chrome-plated plastic plug

- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded

Norms EN 274





# Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)
A564CRM1	8595580522476	0,90   10,79   192,7 kg	380×95×210   595×435×395 mm	12   192 pcs

## 2/3 years \*

Warranty

- **Technical specifications** Resistance of odour trap against the pressure 588 Pa
- Flow rate 48,6 l/min
- Overflow flow rate 33,6 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm

