

A565CRM1

Bath pop-up waste and trap, with overflow filler, for thick-walled bathtubs, chrome

Application

For filling the bath by overflow To drain the water from the bath to the waste For thick-walled bathtubs

For bathtubs with drain outlet Ø52 mm


- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 57 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub only control knob visible
- Control shaft made of stainless steel
- Aerator Neoperl easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow

Scope of supply

- Assembly kit
- Chrome-plated brass outlet grid Chrome-plated plastic control knob Chrome-plated plastic plug
- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded

Norms





Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
A565CRM1	8595580522957	0,95 11,40 202,4 kg	380×95×210 595×435×395 mm	12 192 pcs

Warranty

EN 274 2/3 years *

Technical specifications Resistance of odour trap against the pressure 588 Pa

- Flow rate 48,6 l/min
- Overflow flow rate 33,6 l/min
- Thermal resistance 95 °C Odour trap 50 mm