# alca

## A564CRM1-120

### Bath pop-up waste and trap, with overflow filler, chrome

#### Application

For filling the bath by overflow To drain the water from the bath to the waste For bathtubs with drain outlet Ø52 mm For standard size bathtubs

#### Features


- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 120 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws Space-saving design in the bathtub - only control knob visible
- Control shaft made of stainless steel
- Aerator Neoperl – easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow

#### Scope of supply

#### Assembly kit

- Chrome-plated brass outlet grid
- Chrome-plated plastic control knob Chrome-plated plastic plug
- Waste and trap body with overflow
- Profiled seal Odour trap of polypropylene, thermally and chemically resistant, longitudinally
- welded





#### Order number, Logistic information

Code		Weight (piece   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
	EAN			
A564CRM1-120	8595580523763 120 mm	0,98   11,80   208,8 kg	380×95×210   595×435×395 mm	12   192 pcs
Warranty	Norms			
2/3 years *	EN 274			

Technical specifications Resistance of odour trap against the pressure 588 Pa 

Flow rate 48,6 l/min 

Overflow flow rate 33,6 l/min Thermal resistance 95 °C 

.

Odour trap 50 mm