alca

A564CRM2-100

Bath pop-up waste and trap, with overflow filler, chrome

Application

For filling the bath by overflow To drain the water from the bath to the waste For bathtubs with drain outlet Ø52 mm For standard size bathtubs

Features


- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 100 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub only control knob visible
- Control shaft made of stainless steel
- Aerator Neoperl – easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks Wet odour trap with swivel elbow

Scope of supply

- Assembly kit
- Chrome-plated stainless steel outlet grid Chrome-plated plastic control knob Chrome-plated plastic plug

- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded





Order number, Logistic information

Code		Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
	EAN			
A564CRM2-100	8595580523787 100 mm	0,97 11,60 205,5 kg	380×95×210 595×435×395 mm	12 192 pcs
Warranty	Norms			
2/3 years *	EN 274			

Technical specifications Resistance of odour trap against the pressure 588 Pa Flow rate 48,6 l/min

Overflow flow rate 33,6 l/min

Thermal resistance 95 °C

Odour trap 50 mm