

# A565CRM2-80

Bath pop-up waste and trap, with overflow filler, for thick-walled bathtubs, chrome

### Application

For filling the bath by overflow To drain the water from the bath to the waste For thick-walled bathtubs


For bathtubs with drain outlet Ø52 mm

- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 80 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub visible only control knob
- Control shaft made of stainless steel
- Aerator Neoperl easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow

#### Scope of supply

- Assembly kit
- Chrome-plated stainless steel outlet grid
- Chrome-plated plastic control knob Chrome-plated plastic plug
- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded





# Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)
A565CRM2-80	8595580523893 80 mm	1,00   12,05   212,8 kg	380×95×210   595×435×395 mm	12   192 pcs

# 2/3 years \*

Warranty

**Technical specifications** Resistance of odour trap against the pressure 588 Pa

Norms EN 274

- Flow rate 48,6 l/min
- Overflow flow rate 33,6 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm

250 40 70 70 70 70 70 70 70 70 70 7	7550
120	