

A565CRM3-80

Bath pop-up waste and trap, with overflow filler, for thick-walled bathtubs, chrome

Application

For filling the bath by overflow To drain the water from the bath to the waste For thick-walled bathtubs

For bathtubs with drain outlet Ø52 mm

- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 80 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub visible only control knob
- Control shaft made of stainless steel
- Aerator Neoperl easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks

Norms

Wet odour trap with swivel elbow

Scope of supply

- Assembly kit
- Chrome-plated stainless steel outlet grid
- Chrome-plated plastic control knob
- Chrome-plated plastic plug
- Waste and trap body with overflow Order number, Logistic information





Profiled seal		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
A565CRM3-80	8595580523923 80 mm	1,00 12,01 212,2 kg	380×95×210 595×435×395 mm	12 192 pcs

Warranty

EN 274 2/3 years *

Technical specifications

- Resistance of odour trap against the pressure 588 Pa
- Flow rate 48,6 l/min
- Overflow flow rate 33,6 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm