# alca

## A509KM Bath CLICK/CLACK waste and trap, overflow filler, for thick-walled bathtubs, chrome

#### Application

For filling the bath by overflow To drain the water from the bath to the waste For thick-walled bathtubs For bathtubs with drain outlet Ø52 mm


#### Features

- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 57 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub only control knob visible
- Control shaft made of stainless steel
- Aerator Neoperl – easy access and exchange
- Closing waste by CLICK/CLACK
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow

### Scope of supply

- Assembly kit
- Chrome-plated metal plug
- Chrome-plated brass outlet Chrome-plated plastic control knob
- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded





#### Order number, Logistic information

			Weight	Dimensions	Quantity
Code		EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)
A509KM		8595580524005	0,98   11,88   208,7 kg	380×95×210   595×435×395 mm	12   192 pcs
Warranty	Customs code	Norms			
2/3 years *	39229000	EN 274			

#### Technical specifications

Resistance of odour trap against the pressure 588 Pa

- Flow rate 48,6 l/min
- Overflow flow rate 42 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm