

A116/1200 Solomodul

Pre-wall installation system for dry build up (self-supporting)

Application

For open spaces – does not need any supporting structure

For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm

mm

For floor thickness 0–200 mm


For wall-hung WC

Features

- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Frame material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- Suitable for installation of remote or sensor flushing
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable telescopic feet, range 0–150 mm
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from the rear/top
- A frame module for building into plasterboard constructions
- Maintenance work without using any tools
- Installation depth 200 mm

Scope of supply

- Fixation material for fixing the bidet: Threaded rod M12 – 4 pcs, washers – 2 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8x60 – 8 pcs, dowel Ø12 – 8 pcs
- Elbow waste connector HT 90/90 polyethylene, PE-HD
- Service opening cover is simply adjustable, screws 4 pcs
- Cistern with fill and flush valve
- Waste reduction HT 90/110 polyethylene, PE-HD
- End-caps set for protecting the connecting holes during installation of the system
- Self-supporting frame
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal



Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
A116/1200	8595580527150	20,98 20,98 229,8 kg	1195x220x525 – mm	1 10 pcs

Warranty 2/6 years *	Customs code 39229000	Norms EN 14124, EN 14055
--------------------------------	---------------------------------	------------------------------------

Technical specifications

- Recommended range of water pressure 0,3–0,5 MPa
- Functional range of water pressure 0,05–0,8 MPa
- Hygienic reserve 3 l
- Small flush 2,5–3,5 l
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 3 l
- Factory setting of large flush 6 l
- Big flush 6–9 l
- Load test 400 kg