

A565KM3-100

Bath pop-up waste and trap, with overflow filler, for thick-walled bathtubs, metal

Application

For filling the bath by overflow To drain the water from the bath to the waste For thick-walled bathtubs


For bathtubs with drain outlet Ø52 mm

- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 100 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Space-saving design in the bathtub visible only control knob
- Control shaft made of stainless steel
- Aerator Neoperl easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow

Scope of supply

- Assembly kit
- Chrome-plated metal control knob
- Chrome-plated metal plug Chrome-plated brass outlet grid
- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded





Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
A565KM3-100	8595580530976 100 mm	1,30 15,54 268,7 kg	380×95×210 595×435×395 mm	12 192 pcs

2/3 years * 39229000 **Technical specifications**

Warranty

Resistance of odour trap against the pressure 588 Pa

Customs code

Norms

EN 274

- Flow rate 48,6 l/min
- Overflow flow rate 33,6 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm

^{*} For more information about warranty visit https://www.alcadrain.com/warranty. © 2024 Alcadrain s.r.o | Changes in dimensions and design reserved. | www.alcadrain.com