
alca

A566-112122-80

Bath waste and trap for whirlpool bathtubs, chrome





Application

For whirlpool baths To drain the water from the bath to the waste For bathtubs with drain outlet Ø52 mm

Features

- The length of the bathtub trap 80 cm
- Overflow flexi pipe
- Compatible with most whirlpool and pearl systems
- For connection serve two outlets standard elbow
- A part of the bath waste and trap is a mechanism, that when you open the drain outlet concurrently the valves open, so that can easily drain the residual water from the whirlpool bathtub
- Closing waste by pop-up mechanism
- Wet odour trap with swivel elbow
- Scope of supply

Assembly kit

- Chrome-plated stainless steel outlet grid
- Chrome-plated plastic control knob
- Chrome-plated plastic plug
- Standard elbow for connection of HMS 2 pcs
- Waste and trap body with overflow and discharge mechanism for HMS
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally

welded

Order number, Logistic information				
		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
A566-112122-80	8595580532949 112122 mm	0,68 8,14 150,2 kg	380×95×210 590×430×390 mm	12 192 pcs
Warranty	Norms			
2/3 years *	EN 274			

Technical specifications

- Resistance of odour trap against the pressure 588 Pa
- Flow rate 48,6 l/min
- Overflow flow rate 42 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm