

A102/1200V Jádromodul

Pre-wall installation system with ventilation for dry build up
(especially for renovation of concrete panel housing units)

Application

For installation into wooden structures

For installation between two walls

For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm

Preparation for the connection to the ventilation system

For the reconstruction of apartment units

For floor thickness 0–200 mm

For wall-hung WC

Features

- Recommended extraction fan flow rate 30m³/h, pressure 60 Pa and a return valve, the fan must be positioned at least at a height of 1.2 m above the floor
- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Frame material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- Can be connected to a extraction fan (not included)
- Suitable for installation of remote or sensor flushing
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable telescopic feet, range 0–200 mm
- The elbow bend comes fitted with an end-plug
- Odour removal directly from the WC bowl
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from the rear/top
- Maintenance work without using any tools
- Mounting depth 125 mm, with waste elbow 160 mm
- The load is transferred to the side walls, the strut is adjustable in the range 830–1200 mm

Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8x60 – 4 pcs, dowel Ø12 – 4 pcs
- Elbow HT for connection to the ventilation system
- Elbow waste connector HT 90/90 polyethylene, PE-HD
- Service opening cover is simply adjustable, screws 4 pcs
- Cistern with fill and flush valve
- Waste reduction HT 90/110 polyethylene, PE-HD
- End-caps set for protecting the connecting holes during installation of the system
- Self-supporting frame with a crossbeam for anchoring between walls 830–1200 mm
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal
- Plug for plugging the exhaust outlet if not used

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
A102/1200V	8595580536244	16,55 16,55 268,2 kg	1195x530x145 – mm	1 15 pcs
Warranty 2/6 years *	Customs code 39229000	Norms EN 14124, EN 14055		

Technical specifications

- Recommended range of water pressure 0,3–0,5 MPa
- Functional range of water pressure 0,05–0,8 MPa
- Hygienic reserve 3 l
- Small flush 2,5–3,5 l
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 3 l
- Factory setting of large flush 6 l
- Big flush 6–9 l
- Load test 400 kg

