

# A108F/1100

## Mounting frame with cistern for a waste sink with waste connection DN90/110 and faucet

#### Application

For mounting wall fittings

For mounting in front of a support wall or in to a plasterboard construction For a wall-hung waste sink with a spacing of anchor bolts up to 420 mm and

waste connection Ø90/110


#### **Features**

- Dual flush independently adjustable with hygienic reserve
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The frame allows the anchoring to a separate sufficiently strong plasterboard partition, in front of the bearing wall
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable telescopic feet, range 0–200 mm
- Swivel rail for attaching wall fittings with a pitch of 65–150 mm
- Water supply from the rear/top
- For leading Wall Fittings
- Angle valve with the ability to connect to the Mepla piping system
- Maintenance work without using any tools
- Mounting depth 125 mm, with waste elbow 160 mm
- Built-in tanks allows for rinsing the waste sink
- Height adjustable partitions

### Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 2 pcs, washers 4 pcs
  cover 2 pcs, nut 2 pcs, thread protector 2 pcs
- Fixation set: screw Ø8×60 4 pcs, dowel Ø12 4 pcs
- Waste elbow HT 90/110 with a seal
- The 2 piece cover of the service opening is simply adjustable
- Cistern with fill and flush valve
- Connection fittings G1/2"-G1/2"
- Self-supporting frame
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal





### Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)
A108F/1100	8595580542139	15,86   15,86   257,9 kg	1107×515×139   1107×515×139 mm	1   15 pcs

# Warranty Customs code 2/15 years \* 39229000

## Technical specifications

- Recommended range of water pressure 0,3-0,6 MPa
- Functional range of water pressure 0,05-0,8 MPa
- Hygienic reserve 3 I
- Small flush 2,5-3,5 l
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 3 l
- Factory setting of large flush 6 l
- Big flush 6-9 l
- Load test 400 kg