

AM100/1000E Alcamodul

Pre-wall installation system ECOLOGY for building into solid walls

Application

For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm

For wall-hung WC with flushing volume of 2/4 l

For walling in and around the bearing wall – wet process

Features

- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of the polystyrene insulation simplifies the process of walling-in, prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Material support brackets: galvanized metal
- Installation depth adjustable from 20–95 mm
- Mounting height 1062 mm
- Suitable for installation of remote or sensor flushing
- The cistern is made of one piece, thus ensuring 100% impermeability
- Mounting bracket ensures high rigidity of the toilet connection to the wall
- Necessary to wall under or use supporting feet M90
- Dispenser for WC cistern tablets included
- Sliding rail holder for the waste connector can be set to eight positions between 0–93 mm
- Water supply from the rear/top
- Angle valve with the ability to connect to the Mepla piping system
- Dimensions and construction of the console simplify installation
- Maintenance work without using any tools
- Installation depth 125 mm
- Water-saving flushing: 2 l small flush, 4 l large flush

Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8x60 – 2 pcs, screw Ø4,8x38 – 2 pcs, dowel Ø12 – 2 pcs, dowel Ø8 – 2 pcs
- Elbow waste connector HT 90/110 polyethylene, PE-HD
- The 2 piece cover of the service opening is simply adjustable
- Cistern with fill and flush valve
- Mounting bracket
- End-caps set for protecting the connecting holes during installation of the system
- Set for inserting toilet tablets
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Telescopic mounting brackets 2 pcs
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
AM100/1000E	8595580550554	7,29 7,29 165,7 kg	1045x140x475 1045x475x140 mm	1 20 pcs

Warranty

2/15 years *

Customs code

39229000

Norms

EN 14124, EN 14055

Technical specifications

- Recommended range of water pressure 0,3-0,5 MPa
- Functional range of water pressure 0,05-1,6 MPa
- Hygienic reserve 2 l
- Small flush 2-4 l
- Water volume in the cistern 6 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 2 l
- Factory setting of large flush 4 l
- Big flush 3,5-6 l
- Load test 400 kg

