

AM116/1300H Solomodul

Pre-wall installation system for dry build up (self-supporting) – for people with reduced mobility

Application

For open spaces – does not need any supporting structure
For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230

mm

To mount supporting handrails

For persons with reduced mobility with the recommended use of remote or

sensor flushing

For floor thickness 0–200 mm

For wall-hung WC

Features

- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Frame material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- Suitable for installation of remote or sensor flushing
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable anchor feet and a spring-lock system, with a range of 0–200 mm
- Dispenser for WC cistern tablets included
- Sliding rail holder for the waste connector can be set to eight positions between 0–93 mm
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from the rear/top
- Frame for wall-hung WC in an open space area and boards for the installation of handrails for the disabled
- A frame module for building into plasterboard constructions
- Angle valve with the ability to connect to the Mepla piping system
- Maintenance work without using any tools
- Installation depth 200 mm
- Visible marks for both leveling and the centerline

Scope of supply

- Boards for installing handrails for the disabled
- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8x60 - 16 pcs, anchor Ø12 - 16 pcs
- Elbow waste connector HT 90/110 polyethylene, PE-HD
- The 2 piece cover of the service opening is simply adjustable
- Cistern with fill and flush valve
- End-caps set for protecting the connecting holes during installation of the system
- Set for inserting toilet tablets
- Self-supporting frame
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
AM116/1300H	8595580550585	46,04 46,04 250,2 kg	1010x1285x210 1010x210x1285 mm	1 5 pcs

Warranty	Customs code	Norms
2/15 years *	39229000	EN 14124, EN 14055

Technical specifications

- Recommended range of water pressure 0,3-0,5 MPa
- Functional range of water pressure 0,05-1,6 MPa
- Hygienic reserve 3 l
- Small flush 2,5-3,5 l
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 3 l
- Factory setting of large flush 6 l
- Big flush 6-9 l
- Load test 400 kg

