

# AM101/1120V Sádromodul

Pre-wall installation system with ventilation for dry build up (plasterboard)

### Application

For mounting in front of a support wall or in to a plasterboard construction For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230

#### mm

Preparation for the connection to the ventilation system

For floor thickness 0–200 mm

For wall-hung WC

### Features

- Recommended fan flow rate 30 m<sup>3</sup>/h, a pressure of 60 Pa and a check valve, the fan must be positioned at least at a height of 1.2 m from the floor
- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The frame allows the anchoring to a separate sufficiently strong plasterboard partition, in front of the bearing wall
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Frame material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- Can be connected to a extraction fan (not included)
- Suitable for installation of remote or sensor flushing
- Possibility of tilting the cistern for easy installation in wooden construction buildings or mobile cells
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable anchor feet and a spring-lock system, with a range of 0–200 mm
- Dispenser for WC cistern tablets included
- Odour removal directly from the WC bowl
- Sliding rail holder for the waste connector can be set to eight positions between 0-93 mm
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from the rear/top
- Angle valve with the ability to connect to the Mepla piping system
- Maintenance work without using any tools
- Installation depth 125 mm
- Visible marks for both leveling and the centerline
- Cistern hinges made of two-component material insulate the transmission of vibrations from buildings

## Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 2 pcs, washers 4 pcs
   cover 2 pcs, nut 2 pcs, thread protector 2 pcs
- Fixation set: screw Ø8×60 4 pcs, dowel Ø12 4 pcs
- Elbow HT for connection to the ventilation system
- Elbow waste connector HT 90/90 polyethylene, PE-HD
- The 2 piece cover of the service opening is simply adjustable
- Cistern with fill and flush valve
- Waste reduction HT 90/110 polyethylene, PE-HD
- End-caps set for protecting the connecting holes during installation of the system
- Set for inserting toilet tablets
- Self-supporting frame
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"

Norms

EN 14124, EN 14055

- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal
- Plug for plugging the exhaust outlet if not used

## Order number, Logistic information

AM101/1120V	8595580550615	13.59   13.59   291.7 kg	1130×145×520   1130×520×145 mm	1   20 pcs	
Code	EAN	(piece   packing   palett)	(piece   packing)	(packing   palett)	
		Weight	Dimensions	Quantity	
Order Humber, Logistic information					

# 2/15 years \* 39229000

Warranty

Technical specifications

Recommended range of water pressure 0.3-0.5 MPa

Customs code

- Functional range of water pressure 0,05-1,6 MPa
- Hygienic reserve 3 I
- Small flush 2,5-3,5 I
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 3 I
- Factory setting of large flush 6 I
- Big flush 6-9 l
- Load test 400 kg



	510 50, <i>III</i>	125-250
		G1/2*
alca	ରାତର 🏻	
(min 900)	(220) 135	0110
	90 180 08	Ø110 0 (7) 40 75–168

<sup>\*</sup> For more information about warranty visit https://www.alcadrain.com/warranty.
© 2024 Alcadrain s.r.o | Changes in dimensions and design reserved. | www.alcadrain.com