



M371SB

Flush plate with sensor for pre-wall installation systems, chrome-polished (DC battery operated)



Application

Can not be used for pre-wall installation systems AM118 and AM119, with top actuation

Can not be used for pre-wall installation systems Slim

For touchless flushing with a sensor

For pre-wall installation systems and concealed WC cisterns

Features

- Magnetic switch for service setting and cleaning
- Material: plastic
- Option to use the button for a large flush
- Battery power is included in packaging
- Setting via mini USB using free software available on the Alca website
- Adjustable parameters: start and end time of registration, duration of flushing, automatic flush, allowing flooding, flooding time, variable settings hygienic rinse
- Surface finish: chrome-polished

Scope of supply

- Infrared sensor
- Connector for attaching to the battery
- Case for alc. batteries 6V
- Screw set with a solenoid valve
- Flush plate
- Fixing frame of the flush plate
- Flush valve for sensor flushing
- Threaded frame clamp 2 pcs

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
M371SB	8595580556099	2,40 24,00 404,1 kg	315×210×120 315×120×210 mm	10 160 pcs

Warranty	Customs code	Norms
2/2 years *	84818019	EN 55014, EN 55022, EN 61000

Technical specifications

- Operating force < 20 N
- Power consumption 8,5 W
- Output voltage 6 V