

A564BLACK-80

Bath pop-up waste and trap, with overflow filler, black-matt

Application


For filling the bath by overflow To drain the water from the bath to the waste For bathtubs with drain outlet Ø52 mm For standard size bathtubs

- Side G1/2" fitting for filling of pre-mixed water
- The length of the bathtub trap 80 cm
- Overflow flexi pipe
- Easy installation with three stainless steel screws
- Material: metal with black-matt finish
- Space-saving design in the bathtub visible only control knob
- Control shaft made of stainless steel
- Aerator Neoperl easy access and exchange
- Closing waste by pop-up mechanism
- Bath overflow filler, waste and trap system
- Water does not flow down on the side of the bathtub and does not leave marks
- Wet odour trap with swivel elbow

Scope of supply

- Assembly kit
- Chrome-plated metal control know with black-matt finish
- Chrome-plated metal plug with black-matt finish
- Chrome-plated brass outlet grid with black-matt finish
- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded





Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
A564BLACK-80	8595580561451 80 mm	1,20 14,41 250,6 kg	380×95×210 595×435×395 mm	12 192 pcs

Warranty

Norms 2/3 years * EN 274

Technical specifications

- Resistance of odour trap against the pressure 588 Pa
- Flow rate 48,6 l/min
- Overflow flow rate 33,6 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm

^{*} For more information about warranty visit https://www.alcadrain.com/warranty. © 2024 Alcadrain s.r.o | Changes in dimensions and design reserved. | www.alcadrain.com