


# A516KM-80

Bath CLICK/CLACK waste and trap with flat overflow, chrome



## Application

To drain the water from the bath to the waste  
For design thin-walled freestanding bathtubs  
For bathtubs with drain outlet Ø52 mm  
For standard size bathtubs

## Features

- The length of the bathtub trap 80 cm
- Overflow flexi pipe
- Reduced installation height
- Closing waste by CLICK/CLACK
- Bath waste and overflow system
- Wet odour trap with swivel elbow

## Scope of supply

- Assembly kit
- Chrome-plated metal grid and overflow cover
- Chrome-plated metal plug
- Chrome-plated brass outlet
- Waste and trap body with overflow
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant

## Order number, Logistic information

Code	EAN	Weight (piece   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
A516KM-80	8595580561918	0,72   8,58   157,3 kg	220x360x75   590x430x390 mm	12   192 pcs

Warranty 2/3 years \* Customs code 39229000

## Technical specifications

- Resistance of odour trap against the pressure 588 Pa
- Flow rate 48,6 l/min
- Overflow flow rate 42 l/min
- Thermal resistance 95 °C
- Odour trap 43 mm