

# AM101/1120W Sádromodul

## Pre-wall installation system for dry build up (plasterboard)

### Application

- For mounting into wooden buildings
- For mounting in front of a support wall or in to a plasterboard construction
- For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm
- For wall or floor thickness of 0–200 mm
- For wall-hung WC

### Features

- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The construction of the frame allows anchoring to separate sufficiently load bearing plasterboard partitions or in front of a support wall or side anchoring to wooden frames
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Frame material: powder-coated metal
- Installation depth adjustable from 20–95 mm
- Suitable for installation of remote or sensor flushing
- Possibility of tilting the cistern for easy installation in wooden construction buildings or mobile cells
- The cistern is made of one piece, thus ensuring 100% impermeability
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- Adjustable anchor feet and a spring-lock system, with a range of 0–200 mm
- Sliding rail holder for the waste connector can be set to eight positions between 0–93 mm
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from rear / top / side / inside cistern
- Angle valve with the ability to connect to the Mepla piping system
- Maintenance work without using any tools
- Installation depth 125 mm
- Visible marks for both leveling and the centerline
- Cistern hinges made of two-component material insulate the transmission of vibrations from buildings

### Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8x60 – 4 pcs, dowel Ø12 – 4 pcs
- Elbow waste connector HT 90/90 polyethylene, PE-HD
- The 2 piece cover of the service opening is simply adjustable
- Cistern with fill and flush valve
- Waste reduction HT 90/110 polyethylene, PE-HD
- End-caps set for protecting the connecting holes during installation of the system
- Self-supporting frame
- Fittings 1/2" water connection with the integrated angle valve Schell 1/2–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal

### Order number, Logistic information

Code	EAN	Weight (piece   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
AM101/1120W	8595580564025	14,32   14,32   234,8 kg	1130x145x520   1130x520x145 mm	1   15 pcs

Warranty	Customs code	Norms
2/15 years *	39229000	EN 14124, EN 14055

### Technical specifications

- Recommended range of water pressure 0,05-1,6 MPa
- Functional range of water pressure 0,3-0,5 MPa
- Hygienic reserve 3 l
- Small flush 2-4 l
- Water volume in the cistern 9 l
- Water connection G1/2 "
- Factory setting of small flush 2 l
- Factory setting of large flush 4 l
- Big flush 3,5-6 l
- Load test 400 kg

