

APZ15-850 Marble

Shower drain without edge with grid for embedding tiles

Application

For wheelchair access

For drainage of floor-level showers

For installation into open spaces or near the wall of the shower area

For use of various types of floor coverings


Features

- Elegant design thanks to the grid for embedding tiles without a stainless steel frame
- The collar and trap are protected by foil, and the channel itself by a polystyrene insert
- Trap material: polypropylene
- Shower drain material: stainless steel 2 mm, AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Possibility to buy a combined odour trap
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Self-adhesive tape for quality waterproofing
- Trap firmly connected to the drain 100% waterproofing
- Installation height from 100 mm
- Adjustable height
- The high flow rate is achieved due to the double compartment trap system
- 25 years guarantee

Scope of supply

- Dismantling hook
- Fixation set: screws Ø6×50 2 pcs, dowels Ø10 2 pcs
- Installation trough cover polystyrene
- Protective foil covering for the drain edges and odour trap
- Protective film for trap inlet
- $\stackrel{\cdot}{\operatorname{Grid}}$ for gluing various types of floor coverings
- Template for cutting tiles on the grid
- Self-adhesive waterproofing tape
- The shower drain is assembled with the odour trap





Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
APZ15-850	8595580565565 850 mm	5,48 43,87 151,6 kg	920×205×160 mm	8 24 pcs

Warranty

Norms

2/25 years * EN 1253

Technical specifications

- Total installation height 100-158 mm
- Minimum thickness of concrete 100 mm
- Resistance of odour trap against the pressure 982 Pa
- Waste pipe diameter 50 mm
- Flow rate 60-68,8 I/min
- Load class K3 300 kg
- Odour trap 50 mm

