

# APZ5-TWIN+AEZ121-750 Spa

Waste system for installation in walls, cover for embedding tiles, lighting blue

## Application

For wheelchair access  
 For installation into the wall  
 For indoor use  
 Suitable for areas with movement of large number of people – swimming pools, spa, wellness center

## Features

- Colour illumination – blue
- Easily removable cover - for tile insertion into the thickness of 12 mm
- The collar and trap are protected by foil, and the channel itself by a polystyrene insert
- Trap material: polypropylene
- Material of drainage channel: stainless steel AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Possibility to buy a combined odour trap
- Powered by the electric supply, the power source must be purchased separately – AEZ310, AEZ311 or AEZ320
- LED lighting strip, which is incorporated into the body of the linear drain
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Self-adhesive tape for quality waterproofing
- Trap firmly connected to the drain – 100% waterproofing
- Installation depth 64 mm
- The system is placed outside the area of mechanical stress
- Water flows into the drain only between the edge of the floor tiles and the cover of the drain system
- The high flow rate is achieved due to the double compartment trap system
- 25 years guarantee

## Scope of supply

- Fixing hardware for anchoring the adjustable legs: screw M6x12 – 2 pcs
- Anchoring set: screw Ø6x50 – 2 pcs, dowel Ø10 – 2 pcs, screw Ø4.2x38 – 3 pcs, dowel Ø8 – 3 pcs
- Installation channel cover
- Stainless steel cover for embedding tiles
- The collar and the odour trap inlet are covered by the protective foil
- Showed drain illumination: blue
- Self-adhesive waterproofing tape
- The shower drain is assembled with the odour trap

## Order number, Logistic information

| Code                 | EAN           | Weight<br>(piece   packing   palett) | Dimensions<br>(piece   packing) | Quantity<br>(packing   palett) |
|----------------------|---------------|--------------------------------------|---------------------------------|--------------------------------|
| APZ5-TWIN+AEZ121-750 | 8595580570385 | 121 mm<br>5,12   40,96   142,9 kg    | 720x160x205   mm                | 8   24 pcs                     |

## Warranty

2/25 years \*

## Norms

EN 1253

## Technical specifications

- Total installation height 165-220 mm
- Minimum thickness of concrete 100 mm
- Resistance of odour trap against the pressure 982 Pa
- Waste pipe diameter 50 mm
- Flow rate 60-68,8 l/min
- Cover width 60 mm
- Installation depth 64 mm
- Odour trap 50 mm

