
alca

APV32BLACK

Floor drain 105×105/50 mm straight outlet, stainless steel grid black-matt, combined odour trap SMART





Application

For wheelchair access

For drainage of floor level showers

For the interior, where it is not expected to regularly use the drain (laundry, boiler rooms, cellars)

Features

- Color: black-matt
- Side connection to waste Ø50 mm
- Insulation collar for connection to waterproofing of the building
- Combined odour trap SMART
- Compatibility with floor drains parts including wet, dry and combined odour trap SMART
- Material: polypropylene resistant to mechanical, chemical and thermal damage
- Material: stainless steel AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Stainless steel grid 102×102×5 mm
- Water column and mechanical flap effectively prevent the penetration of odours
- from the sewer
- Height adjustable throat 9–95 mm

Scope of supply

- Design stainless steel grid •
- Floor drain throat 105×105 mm
- Combined odour trap SMART
- Seal kit
- Drain body Ø50 mm, straight outlet

Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
APV32BLACK	8595580574956	0,45 9,05 164,8 kg	160×160×138 590×430×390 mm	20 320 pcs
Warranty	Norms			
2/6 years *	EN 1253			

2/6 years *

- **Technical specifications**
- Total installation height 138-224 mm
- Waste pipe diameter 50 mm
- Flow of the inlet grid 37 l/min
- Load class K3 300 kg
- Odour trap 30 mm