


APZ19BLACK-550 Simple

Shower drain with an edge for two-sided grid, black-matt





Application

For wheelchair access

For drainage of floor-level showers

For installation into open spaces or near the wall of the shower area For indoor use

For embedding tiles or waterproof wood to the thickness of 8 mm

Features

- Secure connection to the construction waterproofing system
- Combined odour trap provides protection against odour from the sewage even after the water dries out from the waste
- Material: polypropylene filled with talc resistant to mechanical, chemical and thermal damage
- Mechanically cleanable trap up to the waste pipe
- They are made of highly durable plastic that resists frost and chemistry
- Grid is included in packaging
- Adjustable plastic anchoring legs 0–35 mm allowing fast and convenient installation, including the precise setting of the required level

Scope of supply

- Fixation set: screw Ø4,2×38 4 pcs, dowel Ø8 4 pcs
- Combined odour trap SMART
- Two-sided grid DOUBLE (full grid or grid for embedding tiles)
- Self-adhesive waterproofing tape
 Height adjustable feet 2 pcs
- Height adjustable feet 2 p
 Linear shower drain
- Linear shower drain

Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
APZ19BLACK-550	8595580583378 550 mm	1,36 61,07 142,1 kg	670×75×155 1180×673×415 mm	45 90 pcs

Warranty

2/6 years *

Technical specifications

- Total installation height 75-110 mm
- Minimum thickness of concrete 62 mm
- Waste outlet diameter 40 mmFlow of the inlet grid 24 l/min
- Odor trap combined with a water seal 25 mm