


# APZ20-650 Simple

Shower drain with a stainless steel edge for two-sided grid



## Application

- For wheelchair access
- For drainage of floor-level showers
- For installation into open spaces or near the wall of the shower area
- For indoor use
- For embedding tiles or waterproof wood to the thickness of 8 mm

## Features

- Secure connection to the construction waterproofing system
- Combined odour trap provides protection against odour from the sewage even after the water dries out from the waste
- Material: polypropylene filled with talc resistant to mechanical, chemical and thermal damage
- Mechanically cleanable trap up to the waste pipe
- They are made of highly durable plastic that resists frost and chemistry
- Grid is included in packaging
- Adjustable plastic anchoring legs 0–35 mm allowing fast and convenient installation, including the precise setting of the required level

## Scope of supply

- Fixation set: screw Ø4,2x38 – 4 pcs, dowel Ø8 – 4 pcs
- Combined odour trap SMART
- Two-sided grid DOUBLE (full grid or grid for embedding tiles)
- Self-adhesive waterproofing tape
- Height adjustable feet 2 pcs
- Linear shower drain

## Order number, Logistic information

Code	EAN	Weight (piece   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
APZ20-650	8595580583484	650 mm 1,75   78,81   157,6 kg	765x80x145   1176x768x410 mm	45   90 pcs

Warranty 2/6 years \* Customs code 39229000

## Technical specifications

- Total installation height 75-110 mm
- Minimum thickness of concrete 62 mm
- Waste outlet diameter 40 mm
- Flow of the inlet grid 24 l/min
- Odor trap combined with a water seal 25 mm