


# APZ20-750 Simple

Shower drain with a stainless steel edge for two-sided grid



## Application

- For wheelchair access
- For drainage of floor-level showers
- For installation into open spaces or near the wall of the shower area
- For indoor use
- For embedding tiles or waterproof wood to the thickness of 8 mm

## Features

- Secure connection to the construction waterproofing system
- Combined odour trap provides protection against odour from the sewage even after the water dries out from the waste
- Material: polypropylene filled with talc resistant to mechanical, chemical and thermal damage
- Mechanically cleanable trap up to the waste pipe
- They are made of highly durable plastic that resists frost and chemistry
- Grid is included in packaging
- Adjustable plastic anchoring legs 0–35 mm allowing fast and convenient installation, including the precise setting of the required level

## Scope of supply

- Fixation set: screw  $\text{Ø}4.2 \times 38$  – 8 pcs, dowel  $\text{Ø}8$  – 8 pcs
- Combined odour trap SMART
- Two-sided grid DOUBLE (full grid or grid for embedding tiles)
- Self-adhesive waterproofing tape
- Height adjustable feet 4 pcs
- Linear shower drain

## Order number, Logistic information

Code	EAN		Weight (piece   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
APZ20-750	8595580583491	750 mm	2,23   66,76   220,3 kg	865x80x145   880x780x410 mm	30   90 pcs

## Warranty

2/6 years \*

## Technical specifications

- Total installation height 75–110 mm
- Minimum thickness of concrete 62 mm
- Waste outlet diameter 40 mm
- Flow of the inlet grid 24 l/min
- Odor trap combined with a water seal 25 mm